



Surface Cleaning and Maintenance polymer-concrete Granit / Uni gloss

Please read the text carefully before maintenance!
Protect your eyes and hands during the work.

1. Surface cleaning

- Clean only with water, liquid soap, Ajax or similar liquid detergents. You can also use a non-abrasive sponge (but not the rough side of a dish sponge).
- Do not use abrasive agents such as ATA etc.
- The wash basin gets a new shine if polished with the polishing paste and some water at a damp soft cloth either by hand or with a rotating felt pad (polishing machine with speed control at medium rotation speeds).
- Make sure you use the polishing paste sparingly otherwise it doesn't polish but smear.

2. Removing stains

Treat the stains as soon as possible with water, liquid soap and similar agents!

- You can use acetone or nail polish remover to treat stubborn stains.
- If removing the stains this way fails use the fine P600 and P800 sand paper dry and then P1000 and P2000 wet.
- Polish it slightly with polishing paste afterwards.

Rinse well after each maintenance!

3. Removing scratches, burnt spots etc.

- Sand the damaged spot with fine P600 and P800 sand paper until smooth and flat.
- Polish it slightly with polishing paste afterwards.

Rinse well after each maintenance!

To remove larger cracks, deeper scratches and other damages you need a **special repair kit** (including instructions) from the manufacturer.

Warning

- Make sure that the water temperature never exceeds 65 °C.
- Don't use acid or leach agents to clean the surface. Use them to clean the outlet pipe only.

The surface of the material can be restored after a certain time (by sanding and polishing the surface).